

EXHIBIT A



US00995364B2

(12) **United States Patent**
Sadkin et al.

(10) **Patent No.:** **US 9,953,646 B2**
(45) **Date of Patent:** **Apr. 24, 2018**

(54) **METHOD AND SYSTEM FOR DYNAMIC SPEECH RECOGNITION AND TRACKING OF PREWRITTEN SCRIPT**

(58) **Field of Classification Search**
CPC G06F 3/0237
See application file for complete search history.

(71) Applicant: **Belleau Technologies, New York, NY (US)**

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,718,094 A 1/1988 Bahl et al.
4,827,521 A 5/1989 Bahl et al.
5,195,167 A 3/1993 Bahl et al.
(Continued)

(72) Inventors: **Eric Sadkin, New York, NY (US);
Lakshmi Kaushik, Irving, TX (US);
Jasjeet Gill, New York, NY (US); Etay
Luz, Miami Beach, FL (US)**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 205 days.

OTHER PUBLICATIONS

Abdulhamid, et al., "Treemaps to Visualise and Navigate Speech Audio" OZCHI '13, Nov. 25-29 2013, Adelaide, Australia Copyright 2013 ACM, p. 555-564.*

(Continued)

(21) Appl. No.: **14/843,923**

(22) Filed: **Sep. 2, 2015**

(65) **Prior Publication Data**
US 2016/0062970 A1 Mar. 3, 2016

Primary Examiner Amelia Tapp
(74) *Attorney, Agent, or Firm* — Kevin Keener, Keener and Associates P.C.

Related U.S. Application Data

(60) Provisional application No. 62/044,506, filed on Sep. 2, 2014.


(51) **Int. Cl.**
G06F 17/00 (2006.01)
G10L 15/22 (2006.01)
G06F 17/21 (2006.01)
G06F 17/27 (2006.01)
G06F 3/023 (2006.01)
G10L 15/197 (2013.01)

(57) **ABSTRACT**

A computer-implemented method for dynamically presenting a prewritten text in a graphical user interface is disclosed. The method comprises receiving a text artifact, storing the text artifact in a memory device of a computer, retrieving the text artifact, displaying the text artifact on the display screen of the computer, receiving a vocal input, generating a text file representing the words spoken in the vocal input, comparing a predetermined number of the hypothesis words to a predetermined number of the artifact words, determining a match location in the text artifact where a specific number of the predetermined number of hypothesis words match a specific number of the predetermined number of artifact words, and altering the display on the display screen to display the match location on the display screen of the computer.

(52) **U.S. Cl.**
CPC **G10L 15/22** (2013.01); **G06F 17/211** (2013.01); **G06F 17/212** (2013.01); **G06F 17/2785** (2013.01); **G06F 3/0237** (2013.01); **G10L 15/197** (2013.01); **G10L 2015/225** (2013.01)

20 Claims, 10 Drawing Sheets



US 9,953,646 B2

Page 2

(56)

References Cited

U.S. PATENT DOCUMENTS

5,276,766 A	1/1994	Bahl et al.	6,928,619 B2	8/2005	Clow et al.
5,572,570 A	11/1996	Kuenzig	6,934,683 B2	8/2005	Ju et al.
5,604,839 A	2/1997	Acero et al.	6,957,184 B2	10/2005	Schmid et al.
5,627,939 A	5/1997	Huang et al.	6,961,694 B2	11/2005	Schmid et al.
5,655,945 A	8/1997	Jani	6,965,863 B1	11/2005	Zuberec et al.
5,657,380 A	8/1997	Mozer	6,973,427 B2	12/2005	Hwang et al.
5,715,369 A	2/1998	Spoltman et al.	6,983,247 B2	1/2006	Ringger et al.
5,745,873 A	4/1998	Braida et al.	6,983,252 B2	1/2006	Matheson et al.
5,787,394 A	7/1998	Bahl et al.	6,988,072 B2	1/2006	Horvitz
5,819,222 A	10/1998	Smyth et al.	7,016,838 B2	3/2006	Rockenbeck et al.
5,829,000 A	10/1998	Huang et al.	7,016,847 B1	3/2006	Tessel et al.
5,878,390 A	3/1999	Kawai et al.	7,031,918 B2	4/2006	Hwang
5,884,258 A	3/1999	Rozak et al.	7,047,189 B2	5/2006	Acero et al.
5,899,976 A	5/1999	Rozak	7,050,975 B2	5/2006	Deng et al.
5,933,804 A	8/1999	Huang et al.	7,058,573 B1	6/2006	Murveit et al.
5,950,160 A	9/1999	Rozak	7,062,436 B1	6/2006	Odell et al.
5,956,671 A	9/1999	Ittycheriah et al.	7,069,216 B2	6/2006	DeMoortel et al.
5,963,903 A	10/1999	Hon et al.	7,072,838 B1	7/2006	Ghosh et al.
5,970,449 A	10/1999	Allewa et al.	7,076,422 B2	7/2006	Hwang
5,983,190 A	11/1999	Trower, II et al.	7,085,710 B1	8/2006	Beckert et al.
6,044,344 A	3/2000	Kanevsky	7,085,716 B1	8/2006	Even et al.
6,055,498 A	4/2000	Neumeyer et al.	7,092,884 B2	8/2006	Lewis et al.
6,076,056 A	6/2000	Huang et al.	7,103,544 B2	9/2006	Mahajan et al.
6,141,641 A	10/2000	Hwang et al.	7,113,950 B2	9/2006	Brill et al.
6,181,351 B1	1/2001	Merrill et al.	7,120,477 B2	10/2006	Huang
6,185,538 B1*	2/2001	Schulz	7,149,970 B1	12/2006	Pratley et al.
		G11B 27/034	7,155,392 B2	12/2006	Schmid et al.
		704/235	7,162,423 B2	1/2007	Thrasher et al.
6,219,643 B1	4/2001	Cohen et al.	7,167,831 B2	1/2007	Falcon et al.
6,226,615 B1*	5/2001	Kirby	7,174,288 B2	2/2007	Ju et al.
		H04N 5/2222	7,174,294 B2	2/2007	Schmid et al.
		348/E5.023	7,177,807 B1	2/2007	Schmid et al.
6,246,981 B1	6/2001	Papineni et al.	7,177,813 B2	2/2007	Schmid et al.
6,260,011 B1	7/2001	Heckerman et al.	7,181,387 B2	2/2007	Ju et al.
6,262,730 B1	7/2001	Horvitz et al.	7,197,132 B2	3/2007	Dezono et al.
6,263,308 B1	7/2001	Heckerman et al.	7,197,459 B1	3/2007	Harinarayan et al.
6,292,857 B1	9/2001	Sidoroff et al.	7,206,389 B1	4/2007	Dumoulin et al.
6,298,324 B1	10/2001	Zuberec et al.	7,206,742 B2	4/2007	Schmid et al.
6,301,560 B1	10/2001	Masters	7,219,085 B2	5/2007	Buck et al.
6,308,155 B1	10/2001	Kingsbury et al.	7,240,011 B2	7/2007	Horvitz
6,324,513 B1	11/2001	Nagai et al.	7,243,070 B2	7/2007	Hoffmann et al.
6,336,108 B1	1/2002	Thiesson et al.	7,251,315 B1	7/2007	Quinton
6,356,867 B1	3/2002	Gabai et al.	7,251,322 B2	7/2007	Stokes, III et al.
6,363,347 B1	3/2002	Rozak	7,251,600 B2	7/2007	Ju et al.
6,374,221 B1	4/2002	Haimi-Cohen	7,263,489 B2	8/2007	Cohen et al.
6,415,258 B1	7/2002	Reynar et al.	7,266,495 B1	9/2007	Beaufays et al.
6,418,431 B1	7/2002	Mahajan et al.	7,272,557 B2	9/2007	Odell
6,434,523 B1	8/2002	Monaco	7,274,741 B2	9/2007	Ma et al.
6,434,527 B1	8/2002	Horvitz	7,275,034 B2	9/2007	Odell et al.
6,434,529 B1	8/2002	Walker et al.	7,283,621 B2	10/2007	Quinton
6,456,975 B1	9/2002	Chang	7,283,850 B2	10/2007	Granovetter et al.
6,477,493 B1	11/2002	Brooks et al.	7,289,950 B2	10/2007	Bellegarda et al.
6,490,563 B2	12/2002	Hon et al.	7,289,956 B2	10/2007	Yu et al.
6,496,795 B1	12/2002	Malvar	7,292,689 B2	11/2007	Odinak et al.
6,502,066 B2	12/2002	Phumpe	7,292,975 B2	11/2007	Lovance et al.
6,502,072 B2	12/2002	Jiang et al.	7,292,986 B1	11/2007	Venolia et al.
6,505,159 B1	1/2003	Theodore	7,299,181 B2	11/2007	Ju et al.
6,539,353 B1	3/2003	Jiang et al.	7,315,818 B2	1/2008	Stevens et al.
6,542,866 B1	4/2003	Jiang et al.	7,319,960 B2	1/2008	Riis et al.
6,571,210 B2	5/2003	Hon et al.	7,343,290 B2	3/2008	Breuer
6,581,033 B1	6/2003	Reynar et al.	7,346,510 B2	3/2008	Deng
6,629,073 B1	9/2003	Hon et al.	7,349,849 B2	3/2008	Silverman et al.
6,662,158 B1	12/2003	Hon et al.	7,349,851 B2	3/2008	Zuberec et al.
6,668,243 B1	12/2003	Odell	7,356,409 B2	4/2008	Quinton
6,694,296 B1	2/2004	Allewa et al.	7,363,229 B2	4/2008	Falcon et al.
6,697,777 B1	2/2004	Ito et al.	7,369,997 B2	5/2008	Chambers et al.
6,782,357 B1	8/2004	Goodman et al.	7,376,586 B1	5/2008	Partovi et al.
6,782,362 B1	8/2004	Hon et al.	7,379,867 B2	5/2008	Chelba et al.
6,782,364 B2	8/2004	Horvitz	7,379,874 B2	5/2008	Schmid et al.
6,856,956 B2	2/2005	Thrasher et al.	7,383,181 B2	6/2008	Huang et al.
6,859,802 B1	2/2005	Rui	7,389,153 B2	6/2008	Gaiimo, III et al.
6,876,966 B1	4/2005	Deng et al.	7,389,234 B2	6/2008	Schmid et al.
6,879,952 B2	4/2005	Acero et al.	7,389,475 B2	6/2008	Clow et al.
6,882,707 B2	4/2005	Engelke et al.	7,391,860 B2	6/2008	Odinak et al.
6,904,402 B1	6/2005	Wang et al.	7,409,349 B2	8/2008	Wang et al.
6,917,918 B2	6/2005	Rockenbeck et al.	7,418,383 B2	8/2008	Droppo et al.
6,920,425 B1	6/2005	Will et al.	7,421,386 B2	9/2008	Powell et al.
			7,428,491 B2	9/2008	Wang et al.
			7,437,290 B2	10/2008	Danieli

US 9,953,646 B2

Page 3

(56)

References Cited

U.S. PATENT DOCUMENTS

7,451,083 B2	11/2008	Frey et al.	7,689,420 B2	3/2010	Paek et al.
7,451,389 B2	11/2008	Huynh et al.	7,689,426 B2	3/2010	Marula
7,454,336 B2	11/2008	Attias et al.	7,702,503 B2	4/2010	Monkowski
7,454,344 B2	11/2008	Ramsey	7,702,512 B2	4/2010	Gopinath et al.
7,460,992 B2	12/2008	Droppo et al.	7,711,551 B2	5/2010	Lopez-Barquilla et al.
7,461,059 B2	12/2008	Richardson et al.	7,716,057 B2	5/2010	Horvitz
7,475,017 B2	1/2009	Ju et al.	7,720,678 B2	5/2010	Falcon et al.
7,487,087 B2	2/2009	Attias et al.	7,720,679 B2	5/2010	Ichikawa et al.
7,496,513 B2	2/2009	Soong et al.	7,721,301 B2	5/2010	Wong et al.
7,496,693 B2	2/2009	Cook et al.	7,729,917 B2	6/2010	Miyamoto et al.
7,499,857 B2	3/2009	Gunawardana	7,729,919 B2	6/2010	Wang
7,506,022 B2	3/2009	Wang et al.	7,739,221 B2	6/2010	Lawler et al.
7,506,271 B2	3/2009	Wang et al.	7,747,437 B2	6/2010	Verhasselt et al.
7,516,067 B2	4/2009	Seltzer et al.	7,747,440 B2	6/2010	Eide et al.
7,518,631 B2	4/2009	Hershey et al.	7,751,535 B2	7/2010	Creamer et al.
7,519,531 B2	4/2009	Acero et al.	7,752,043 B2	7/2010	Walson
7,519,536 B2	4/2009	Maes et al.	7,752,152 B2	7/2010	Paek et al.
7,533,020 B2	5/2009	Arnold et al.	7,756,708 B2	7/2010	Cohen et al.
7,548,856 B2	6/2009	Thiesson et al.	7,756,802 B2	7/2010	Zhang
7,551,944 B2	6/2009	Barcis et al.	7,778,816 B2	8/2010	Reynar
7,552,221 B2	6/2009	Hennecke	7,778,821 B2	8/2010	Mowatt et al.
7,561,673 B2	7/2009	Wang	7,778,830 B2	8/2010	Davis et al.
7,565,284 B2	7/2009	Deng et al.	7,783,305 B2	8/2010	Ross et al.
7,567,902 B2	7/2009	Davis et al.	7,783,484 B2	8/2010	Deligne et al.
7,571,096 B2	8/2009	Schmid et al.	7,783,488 B2	8/2010	Ben-David et al.
7,571,100 B2	8/2009	Lenir et al.	7,788,103 B2	8/2010	Marcus
7,574,359 B2	8/2009	Huang	7,788,594 B1	8/2010	Tevanian, Jr.
7,580,570 B2	8/2009	Manu et al.	7,801,727 B2	9/2010	Gopalakrishnan et al.
7,587,317 B2	9/2009	Falcon et al.	7,801,756 B1	9/2010	Harinarayan et al.
7,590,533 B2	9/2009	Hwang	7,801,968 B2	9/2010	Wang et al.
7,593,843 B2	9/2009	Auc et al.	7,805,305 B2	9/2010	Badt et al.
7,610,204 B2	10/2009	Ruback et al.	7,805,308 B2	9/2010	Deng et al.
7,610,547 B2	10/2009	Wang et al.	7,809,566 B2	10/2010	Meermeier
7,613,532 B2	11/2009	Anderson et al.	7,809,567 B2	10/2010	Ju et al.
7,617,103 B2	11/2009	Ile et al.	7,813,920 B2	10/2010	Leung et al.
7,617,104 B2	11/2009	Deng et al.	7,813,926 B2	10/2010	Wang et al.
7,624,014 B2	11/2009	Stewart et al.	7,813,929 B2	10/2010	Bisani et al.
7,624,016 B2	11/2009	Ju et al.	7,814,501 B2	10/2010	Lecoeuche et al.
7,624,018 B2	11/2009	Chambers et al.	7,822,608 B2	10/2010	Cross, Jr. et al.
7,624,019 B2	11/2009	Andrew	7,827,033 B2	11/2010	Ativanichayaphong et al.
7,627,638 B1	12/2009	Cohen	7,827,232 B2	11/2010	Bear et al.
7,634,066 B2	12/2009	Quinton	7,831,425 B2	11/2010	Acero et al.
7,634,404 B2	12/2009	Hon et al.	7,831,427 B2	11/2010	Potter et al.
7,634,405 B2	12/2009	Basu et al.	7,840,407 B2	11/2010	Strope et al.
7,634,406 B2	12/2009	Li et al.	7,840,409 B2	11/2010	Ativanichayaphong et al.
7,634,407 B2	12/2009	Chelba et al.	7,844,456 B2	11/2010	Cai et al.
7,636,657 B2	12/2009	Ju et al.	7,844,465 B2	11/2010	Marcus
7,636,661 B2	12/2009	De Leeuw et al.	7,848,314 B2	12/2010	Cross, Jr. et al.
7,640,159 B2	12/2009	Reich	7,852,993 B2	12/2010	Ju et al.
7,640,161 B2	12/2009	Morris et al.	7,856,351 B2	12/2010	Yaman et al.
7,640,272 B2	12/2009	Mahajan et al.	7,860,707 B2	12/2010	Yu et al.
7,643,985 B2	1/2010	Horvitz	7,860,715 B2	12/2010	Essenmacher et al.
7,643,995 B2	1/2010	Acero et al.	7,864,929 B2	1/2011	Carro
7,653,547 B2	1/2010	Kershaw et al.	7,865,357 B2	1/2011	Acero et al.
7,657,432 B2	2/2010	Chaudhari et al.	7,865,364 B2	1/2011	Helbing
7,657,845 B2	2/2010	Drucker et al.	7,870,000 B2	1/2011	Ativanichayaphong et al.
7,660,717 B2	2/2010	Takiguchi et al.	7,873,209 B2	1/2011	Deng et al.
7,664,637 B2	2/2010	Deligne et al.	7,881,930 B2	2/2011	Faisman et al.
7,664,638 B2	2/2010	Cooper et al.	7,881,932 B2	2/2011	Muschett
7,665,041 B2	2/2010	Wilson et al.	7,881,938 B2	2/2011	Muschett et al.
7,668,721 B2	2/2010	Barkley et al.	7,885,811 B2	2/2011	Zimmerman et al.
7,668,867 B2	2/2010	Morris et al.	7,885,812 B2	2/2011	Acero et al.
7,672,832 B2	3/2010	Huang et al.	7,885,817 B2	2/2011	Paek et al.
7,672,847 B2	3/2010	He et al.	7,890,325 B2	2/2011	Liu et al.
7,676,365 B2	3/2010	Hwang et al.	7,890,326 B2	2/2011	Strope et al.
7,676,371 B2	3/2010	Cross, Jr. et al.	7,899,673 B2	3/2011	Brown
7,676,373 B2	3/2010	Miyamoto et al.	7,904,296 B2	3/2011	Morris
7,680,514 B2	3/2010	Cook et al.	7,904,299 B2	3/2011	Gandhi et al.
7,680,661 B2	3/2010	Co et al.	7,908,151 B2	3/2011	Heckerman et al.
7,681,123 B2*	3/2010	Krause	7,912,186 B2	3/2011	Howell et al.
			7,912,700 B2	3/2011	Bower et al.
			7,917,514 B2	3/2011	Lawler et al.
			7,925,502 B2	4/2011	Droppo et al.
			7,925,505 B2	4/2011	Wu
			7,925,512 B2	4/2011	Cross, Jr. et al.
7,684,987 B2	3/2010	Chu et al.	7,941,316 B2	5/2011	Mahajan et al.
7,684,988 B2	3/2010	Barquilla	7,953,597 B2	5/2011	Ativanichayaphong et al.
7,689,413 B2	3/2010	Hershey et al.	7,957,959 B2	6/2011	Han et al.
7,689,419 B2	3/2010	Mahajan et al.	7,957,969 B2	6/2011	Alewine et al.

G06F 3/012
715/255

US 9,953,646 B2

Page 4

(56)

References Cited

U.S. PATENT DOCUMENTS

7,962,337 B2	6/2011	Steinbiss	8,150,692 B2	4/2012	Stewart et al.
7,962,340 B2	6/2011	Comerford et al.	8,150,693 B2	4/2012	Mori et al.
7,962,344 B2	6/2011	Sharpe et al.	8,160,876 B2	4/2012	Dow et al.
7,966,180 B2	6/2011	Bajaj et al.	8,160,878 B2	4/2012	Yu et al.
7,970,608 B2	6/2011	Madhavapeddi et al.	8,165,876 B2	4/2012	Emam et al.
7,974,476 B2	7/2011	Zhang et al.	8,165,877 B2	4/2012	Wang et al.
7,974,842 B2	7/2011	Helbing et al.	8,165,883 B2	4/2012	Galanes et al.
7,983,913 B2	7/2011	Seltzer et al.	8,170,537 B1	5/2012	Bori
7,983,914 B2	7/2011	Lickhart et al.	8,175,872 B2	5/2012	Kristjansson et al.
7,984,035 B2	7/2011	Levin et al.	8,179,419 B2	5/2012	Girish et al.
7,991,607 B2	8/2011	Zhang et al.	8,180,069 B2	5/2012	Buck et al.
7,991,613 B2	8/2011	Blair	8,180,636 B2	5/2012	Droppo et al.
7,991,615 B2	8/2011	Li et al.	8,180,640 B2	5/2012	Li et al.
7,996,225 B2	8/2011	Schmid et al.	8,180,641 B2	5/2012	Levit et al.
8,000,962 B2	8/2011	Doyle et al.	8,185,392 B1	5/2012	Strope et al.
8,000,966 B2	8/2011	Mori et al.	8,190,430 B2	5/2012	Doyle et al.
8,005,683 B2	8/2011	Tessel et al.	8,190,437 B2	5/2012	Farrell et al.
8,009,819 B2	8/2011	Faizakov et al.	8,190,479 B2	5/2012	Surendran et al.
8,010,367 B2	8/2011	Muschett et al.	8,204,746 B2	6/2012	Odinak
8,019,387 B2	9/2011	Barcis et al.	8,209,169 B2	6/2012	Imoto et al.
8,019,591 B2	9/2011	Gao et al.	8,209,175 B2	6/2012	Mukerjee et al.
8,019,602 B2	9/2011	Yu et al.	8,214,215 B2	7/2012	Li et al.
8,019,607 B2	9/2011	Creamer et al.	8,219,384 B2	7/2012	Lloyd et al.
8,024,184 B2	9/2011	Takiguchi et al.	8,219,406 B2	7/2012	Yu et al.
8,024,194 B2	9/2011	Cross, Jr. et al.	8,223,932 B2	7/2012	Forbes et al.
8,024,422 B2	9/2011	Krocker et al.	8,224,644 B2	7/2012	Krumel et al.
8,032,375 B2	10/2011	Chickering et al.	8,224,650 B2	7/2012	Galanes et al.
8,036,889 B2	10/2011	Carus et al.	8,224,656 B2	7/2012	Scholz et al.
8,036,893 B2	10/2011	Reich	8,229,744 B2	7/2012	Dharanipragada et al.
8,036,896 B2	10/2011	Adams, Jr. et al.	8,229,750 B2	7/2012	Creamer et al.
8,041,561 B2	10/2011	Deligne et al.	8,229,753 B2	7/2012	Galanes et al.
8,041,568 B2	10/2011	Strope et al.	8,233,592 B2	7/2012	Gandhi et al.
8,041,570 B2	10/2011	Mirkovic et al.	8,234,111 B2	7/2012	Lloyd et al.
8,046,220 B2	10/2011	Agarwal et al.	8,234,120 B2	7/2012	Agapi et al.
8,046,224 B2	10/2011	Rajput et al.	8,239,195 B2	8/2012	Li et al.
8,060,360 B2	11/2011	He	8,239,203 B2	8/2012	Stubley et al.
8,060,365 B2	11/2011	Itoh et al.	8,239,206 B1	8/2012	LeBeau et al.
8,065,142 B2	11/2011	Imoto et al.	8,239,332 B2	8/2012	Liu et al.
8,065,143 B2	11/2011	Yanagihara	8,239,366 B2	8/2012	Sejnoha et al.
8,065,146 B2	11/2011	Acero et al.	8,244,545 B2	8/2012	Paek et al.
8,065,149 B2	11/2011	Kurata et al.	8,249,868 B2	8/2012	Lloyd et al.
8,069,032 B2	11/2011	Odell et al.	8,249,871 B2	8/2012	Mukerjee
8,069,045 B2	11/2011	Emam et al.	8,254,535 B1	8/2012	Madhavapeddi et al.
8,073,692 B2	12/2011	Ativanichayaphong et al.	8,255,216 B2	8/2012	White
8,073,697 B2	12/2011	Cross, Jr. et al.	8,255,218 B1	8/2012	Cohen et al.
8,074,199 B2	12/2011	Millett et al.	8,255,223 B2	8/2012	Wang
8,079,079 B2	12/2011	Zhang et al.	8,255,293 B1	8/2012	Davies
8,082,148 B2	12/2011	Agapi et al.	8,260,615 B1	9/2012	Nakajima et al.
8,086,455 B2	12/2011	Gong et al.	8,265,928 B2	9/2012	Kristjansson et al.
8,086,460 B2	12/2011	Da Palma et al.	8,266,078 B2	9/2012	Zou et al.
8,086,463 B2	12/2011	Ativanichayaphong et al.	8,271,268 B2	9/2012	Keohane et al.
8,090,077 B2	1/2012	Wang et al.	8,275,618 B2	9/2012	Ganong, III
8,090,738 B2	1/2012	Paek et al.	8,275,619 B2	9/2012	Herbig et al.
8,095,371 B2	1/2012	Horioka et al.	8,275,621 B2	9/2012	Alewine et al.
8,099,279 B2	1/2012	Acero et al.	8,280,733 B2	10/2012	Yu et al.
8,099,287 B2	1/2012	Bodin et al.	8,285,546 B2	10/2012	Reich
8,103,503 B2	1/2012	Duncan	8,290,772 B1	10/2012	Cohen et al.
8,103,646 B2	1/2012	Brown	8,290,775 B2	10/2012	Etezadi et al.
8,108,205 B2	1/2012	Paek et al.	8,296,142 B2	10/2012	Lloyd et al.
8,111,282 B2	2/2012	Cutler et al.	8,296,383 B2	10/2012	Lindahl
8,112,274 B2	2/2012	Beyerlein	8,301,445 B2	10/2012	Gruhn et al.
8,117,032 B2	2/2012	Charoenruangkit et al.	8,301,448 B2	10/2012	Carus et al.
8,121,837 B2	2/2012	Agapi et al.	8,301,449 B2	10/2012	Ife et al.
8,121,838 B2	2/2012	Kobal et al.	8,306,511 B2	11/2012	Ling et al.
8,121,840 B2	2/2012	Chu et al.	8,306,815 B2	11/2012	Konig et al.
8,126,715 B2	2/2012	Paek	8,306,817 B2	11/2012	Yu et al.
8,131,545 B1	3/2012	Moreno et al.	8,306,819 B2	11/2012	Liu et al.
8,131,548 B2	3/2012	Blass	8,306,822 B2	11/2012	Li et al.
8,131,750 B2	3/2012	Bathiche et al.	8,311,822 B2	11/2012	Bahl et al.
8,135,578 B2	3/2012	Hebert	8,311,828 B2	11/2012	Arrowood et al.
8,135,589 B1	3/2012	Reding et al.	8,311,835 B2	11/2012	Lecoeuche
8,145,484 B2	3/2012	Zweig	8,315,874 B2	11/2012	Barton et al.
8,145,488 B2	3/2012	Yu et al.	8,315,878 B1	11/2012	Burns et al.
8,145,494 B2	3/2012	Horioka et al.	8,321,277 B2	11/2012	Coulomb et al.
8,150,687 B2	4/2012	Mori et al.	8,332,218 B2	12/2012	Cross, Jr. et al.
			8,332,225 B2	12/2012	Zhao et al.
			8,332,227 B2	12/2012	Maes et al.
			8,335,683 B2	12/2012	Acero et al.
			8,335,687 B1	12/2012	Redling et al.

US 9,953,646 B2

Page 5

(56)

References Cited

U.S. PATENT DOCUMENTS

8,346,551 B2	1/2013	Herbig et al.	8,515,746 B1	8/2013	Garrett et al.
8,346,554 B2	1/2013	Zlokarnik	8,515,757 B2	8/2013	Cross, Jr. et al.
8,346,555 B2	1/2013	Metz	8,515,758 B2	8/2013	Huo
8,352,245 B1	1/2013	Lloyd	8,515,762 B2	8/2013	Krumel et al.
8,352,246 B1	1/2013	Lloyd	8,515,766 B1	8/2013	Bringert et al.
8,352,276 B1	1/2013	Pettay et al.	8,520,810 B1	8/2013	Reding et al.
8,355,484 B2	1/2013	Eide et al.	8,521,523 B1	8/2013	Garrett et al.
8,355,918 B2	1/2013	Agapi et al.	8,521,526 B1	8/2013	Lloyd et al.
8,355,920 B2	1/2013	Gopinath et al.	8,521,528 B2	8/2013	Odinak
8,359,201 B1	1/2013	Talbot et al.	8,521,539 B1	8/2013	Teng et al.
8,364,481 B2	1/2013	Stroke et al.	8,521,585 B2	8/2013	Quilici et al.
8,370,143 B1	2/2013	Coker	8,527,271 B2	9/2013	Wandinger et al.
8,370,146 B1	2/2013	Schalkwyk et al.	8,532,985 B2	9/2013	Seltzer et al.
8,374,865 B1	2/2013	Biadys et al.	8,532,990 B2	9/2013	Seltzer et al.
8,380,505 B2	2/2013	Konig et al.	8,532,991 B2	9/2013	He et al.
8,380,514 B2	2/2013	Bodin et al.	8,538,754 B2	9/2013	Cohen et al.
8,386,248 B2	2/2013	Dhanakshinr et al.	8,542,810 B2	9/2013	Cohen et al.
8,386,250 B2	2/2013	Lloyd et al.	8,543,398 B1	9/2013	Strope et al.
8,386,251 B2	2/2013	Strom et al.	8,543,404 B2	9/2013	Moore et al.
8,386,254 B2	2/2013	Deshmukh et al.	8,554,559 B1	10/2013	Aleksic et al.
8,391,464 B1	3/2013	Sharp	8,554,755 B2	10/2013	Richardson et al.
8,396,709 B2	3/2013	Lloyd et al.	8,560,310 B1	10/2013	Zhang et al.
8,396,973 B2	3/2013	Wang	8,560,327 B2	10/2013	Neubacher et al.
8,401,846 B1	3/2013	Reding et al.	8,562,434 B2	10/2013	Goller et al.
8,401,852 B2	3/2013	Zweig et al.	8,566,087 B2	10/2013	Cross, Jr. et al.
8,401,854 B2	3/2013	Schwarz	8,566,091 B2	10/2013	Low et al.
8,406,384 B1	3/2013	Tremblay et al.	8,571,851 B1	10/2013	Tickner et al.
8,407,041 B2	3/2013	Deng et al.	8,571,859 B1	10/2013	Aleksic et al.
8,407,050 B2	3/2013	Kobal et al.	8,571,860 B2	10/2013	Strope et al.
8,407,057 B2	3/2013	Comerford et al.	8,571,869 B2	10/2013	Deligne et al.
8,412,526 B2	4/2013	Sorin	8,583,441 B2	11/2013	Berton et al.
8,412,531 B2	4/2013	Sullivan et al.	8,589,157 B2	11/2013	Ju et al.
8,417,527 B2	4/2013	Rajput et al.	8,589,162 B2	11/2013	Lejeune et al.
8,417,530 B1	4/2013	Hayes	8,589,164 B1	11/2013	Mengibar et al.
8,423,359 B2	4/2013	Cohen et al.	8,593,501 B1	11/2013	Kjeldnas
8,423,364 B2	4/2013	Yu et al.	8,599,704 B2	12/2013	Wang et al.
8,428,241 B2	4/2013	Faizkov et al.	8,599,836 B2	12/2013	Van Buren et al.
8,428,940 B2	4/2013	Kristjansson et al.	8,600,742 B1	12/2013	Gruenstein
8,428,944 B2	4/2013	Poultney et al.	8,600,746 B1	12/2013	Lei et al.
8,433,611 B2	4/2013	Lax et al.	8,600,763 B2	12/2013	Brush et al.
8,438,025 B2	5/2013	Bahl et al.	8,606,568 B1	12/2013	Tickner et al.
8,438,026 B2	5/2013	Fischer et al.	8,606,581 B1	12/2013	Quast et al.
8,442,824 B2	5/2013	Aley-Raz et al.	8,611,505 B2	12/2013	Oppenheim et al.
8,442,826 B2	5/2013	Hamaker et al.	8,612,230 B2	12/2013	Agapi et al.
8,442,830 B2	5/2013	Nakajima et al.	8,612,231 B2	12/2013	Grobauer et al.
8,447,599 B2	5/2013	Reding et al.	8,615,388 B2	12/2013	Li et al.
8,447,600 B2	5/2013	Cohen et al.	8,615,393 B2	12/2013	Tashev et al.
8,447,616 B2	5/2013	Falcon et al.	8,620,139 B2	12/2013	Li et al.
8,451,823 B2	5/2013	Ben-David et al.	8,620,652 B2	12/2013	Chambers et al.
8,452,597 B2	5/2013	Bringert et al.	8,620,656 B2	12/2013	Fu et al.
8,452,602 B1	5/2013	Bringert et al.	8,620,657 B2	12/2013	Farrell et al.
8,457,946 B2	6/2013	Kuo et al.	8,620,667 B2	12/2013	Andrew
8,457,967 B2	6/2013	Audkhshi et al.	8,630,860 B1	1/2014	Zhang et al.
8,463,606 B2	6/2013	Scott et al.	8,635,075 B2	1/2014	Andrew
8,463,608 B2	6/2013	Dow et al.	8,644,488 B2	2/2014	Byrd et al.
8,468,012 B2	6/2013	Lloyd et al.	8,645,128 B1	2/2014	Agiomirgiannakis
8,468,022 B2	6/2013	Bringert et al.	8,645,134 B1	2/2014	Harrenstien et al.
8,473,289 B2	6/2013	Jitkoff et al.	8,645,136 B2 *	2/2014	Milstein
8,473,293 B1	6/2013	Mengibar et al.			
8,473,296 B2	6/2013	Grobauer et al.			
8,478,588 B2	7/2013	Da Palma et al.			
8,478,592 B2	7/2013	Patel			
8,484,023 B2	7/2013	Kanevsky et al.			
8,484,024 B2	7/2013	Kanevsky et al.			
8,484,030 B1	7/2013	Pettay et al.			
8,489,398 B1	7/2013	Gruenstein			
8,489,401 B1	7/2013	Pettay			
8,490,016 B2	7/2013	DeMaio et al.			
8,494,848 B2	7/2013	Reding et al.			
8,504,369 B1	8/2013	Chigier et al.			
8,504,371 B1	8/2013	Vacek et al.			
8,509,398 B2	8/2013	Kriese et al.			
8,510,412 B2	8/2013	Krocker et al.			
8,515,736 B1	8/2013	Duta			
8,515,745 B1	8/2013	Garrett et al.			
			8,645,138 B1	2/2014	Weinstein et al.
			8,650,029 B2	2/2014	Thambiratnam et al.
			8,650,031 B1	2/2014	Mamou et al.
			8,650,032 B2	2/2014	Fu et al.
			8,654,933 B2	2/2014	Doulton
			8,660,847 B2	2/2014	Soemo et al.
			8,661,112 B2	2/2014	Creamer et al.
			8,666,726 B2	3/2014	Tremblay et al.
			8,666,743 B2	3/2014	Schwarz et al.
			8,666,745 B2	3/2014	Sallier
			8,666,750 B2	3/2014	Buck et al.
			8,666,963 B2	3/2014	Sejnoha et al.
			8,667,532 B2	3/2014	Heath
			8,670,987 B2	3/2014	Bergl et al.
			8,676,581 B2	3/2014	Flaks et al.
			8,676,904 B2	3/2014	Lindahl
			8,677,236 B2	3/2014	Bower et al.
			8,682,659 B2	3/2014	Kristjansson et al.
			8,682,661 B1	3/2014	Schalkwyk et al.
			8,682,663 B2	3/2014	Reding et al.

G10L 15/06
704/244

US 9,953,646 B2

Page 6

(56)

References Cited

U.S. PATENT DOCUMENTS

8,682,676 B2	3/2014	Burns et al.	8,775,189 B2	7/2014	Burns et al.
8,688,446 B2	4/2014	Yanagihara	8,781,826 B2	7/2014	Koosman
8,688,452 B2	4/2014	Lewis et al.	8,781,832 B2	7/2014	Comerford et al.
8,689,251 B1	4/2014	Heath	8,781,833 B2	7/2014	Duta et al.
8,693,466 B2	4/2014	Johnson	8,793,130 B2	7/2014	Wang et al.
8,694,313 B2	4/2014	Lloyd et al.	8,798,239 B2	8/2014	Stifelman et al.
8,694,316 B2	4/2014	Pickering et al.	8,798,995 B1	8/2014	Edara
8,694,322 B2	4/2014	Snitkovskiy et al.	8,798,997 B2	8/2014	Grobauer et al.
8,700,393 B2	4/2014	Aleksic et al.	8,805,345 B2	8/2014	Ling et al.
8,700,394 B2	4/2014	Seltzer et al.	8,805,684 B1	8/2014	Aleksic et al.
8,700,400 B2	4/2014	Pavey et al.	8,811,592 B1	8/2014	Pettay et al.
8,700,594 B2	4/2014	Apacible et al.	8,812,316 B1	8/2014	Chen
8,705,519 B2	4/2014	Jackson et al.	8,812,325 B2	8/2014	Burns et al.
8,706,483 B2	4/2014	Gerl et al.	8,818,797 B2	8/2014	Acero et al.
8,706,490 B2	4/2014	Cross et al.	8,818,809 B2	8/2014	Reding et al.
8,706,495 B2	4/2014	Gschwendtner	8,825,478 B2	9/2014	Cox et al.
8,706,505 B1	4/2014	Bringert et al.	8,825,481 B2	9/2014	Thambirnam et al.
8,712,757 B2	4/2014	Hamilton, II et al.	8,830,165 B1	9/2014	Heath et al.
8,712,770 B2	4/2014	Fukuda et al.	8,831,185 B2	9/2014	Gandhi et al.
8,712,772 B2	4/2014	Ocz	8,831,930 B2	9/2014	Strope et al.
8,712,774 B2	4/2014	Wiggs	8,831,946 B2	9/2014	Mamou
8,713,119 B2	4/2014	Lindahl	8,831,950 B2	9/2014	Moore et al.
8,719,019 B2	5/2014	Do et al.	8,831,951 B2	9/2014	Cohen
8,719,023 B2	5/2014	Menendez-Pidal et al.	8,831,956 B2	9/2014	Morgan et al.
8,719,024 B1	5/2014	Moreno et al.	8,831,957 B2	9/2014	Taubman et al.
8,719,035 B2	5/2014	Stewart et al.	8,832,804 B1	9/2014	Casey et al.
8,725,492 B2	5/2014	Odell et al.	8,838,434 B1	9/2014	Liu
8,725,505 B2	5/2014	Mowatt et al.	8,838,448 B2	9/2014	Jiang et al.
8,725,512 B2	5/2014	Claiborn et al.	8,838,449 B2	9/2014	Ju et al.
8,731,916 B2	5/2014	Li et al.	8,843,370 B2	9/2014	Willett et al.
8,731,925 B2	5/2014	Da Palma et al.	8,843,376 B2	9/2014	Cross, Jr.
8,731,927 B2	5/2014	Schwarz	8,849,664 B1	9/2014	Lei et al.
8,731,928 B2	5/2014	Rajput et al.	8,849,791 B1	9/2014	Hertschuh et al.
8,731,937 B1	5/2014	Reding et al.	8,856,004 B2	10/2014	Basson et al.
8,731,939 B1	5/2014	Lebeau et al.	8,862,467 B1	10/2014	Casado et al.
8,738,376 B1	5/2014	Goel et al.	8,862,468 B2	10/2014	Pack et al.
8,744,861 B2	6/2014	Ativanichayaphong et al.	8,862,475 B2	10/2014	Ativanichayaphong et al.
8,745,025 B2	6/2014	Sejnoha et al.	8,868,409 B1	10/2014	Mengibar et al.
8,750,463 B2	6/2014	Doulton	8,868,425 B2	10/2014	Maes et al.
8,751,217 B2	6/2014	Ballinger et al.	8,868,428 B2	10/2014	Gruenstein et al.
8,756,175 B1	6/2014	Szedegy	8,874,442 B2	10/2014	Aley-Raz et al.
8,762,150 B2	6/2014	Edgington et al.	8,874,447 B2	10/2014	Da Palma et al.
8,762,152 B2	6/2014	Bennett et al.	8,874,448 B1	10/2014	Kaufmann et al.
8,762,156 B2	6/2014	Chen	8,880,398 B1	11/2014	Aleksic et al.
8,762,469 B2	6/2014	Lindahl	8,886,524 B1	11/2014	Watanabe et al.
8,767,928 B2	7/2014	Springer	8,886,532 B2	11/2014	Levit et al.
8,768,695 B2	7/2014	Tang et al.	2014/0278428 A1 *	9/2014	Rolland
8,768,698 B2	7/2014	Mengibar et al.			G10L 15/26 704/257
8,768,701 B2	7/2014	Cohen et al.			
8,768,723 B2	7/2014	Montyne et al.			
8,768,969 B2	7/2014	Ilucita et al.			
8,774,392 B2	7/2014	Odinak et al.			
8,775,175 B1	7/2014	Nagel et al.			
8,775,180 B1	7/2014	Pettay et al.			
8,775,183 B2	7/2014	Hamaker et al.			

OTHER PUBLICATIONS

Kushalnagar, et al., "Captions Versus Transcripts for Online Video Content" W4A2013—Communication, May 13-15, 2013, Rio de Janeiro, Brazil. Co-Located with the 22nd International World Wide Web Conference. Copyright 2013 ACM, 4 pages.*

* cited by examiner

U.S. Patent

Apr. 24, 2018

Sheet 1 of 10

US 9,953,646 B2




Fig. 1

U.S. Patent

Apr. 24, 2018

Sheet 2 of 10

US 9,953,646 B2




Fig. 2



U.S. Patent

Apr. 24, 2018

Sheet 4 of 10

US 9,953,646 B2




Fig. 4A




Fig. 4B




Fig. 5




Fig. 6




Fig. 7

U.S. Patent

Apr. 24, 2018

Sheet 8 of 10

US 9,953,646 B2




Fig. 8




Fig. 9

U.S. Patent

Apr. 24, 2018

Sheet 10 of 10

US 9,953,646 B2




Fig. 10

US 9,953,646 B2

1

METHOD AND SYSTEM FOR DYNAMIC SPEECH RECOGNITION AND TRACKING OF PREWRITTEN SCRIPT

PRIORITY

This application claims benefit to U.S. Provisional Patent Ser. No. 62/044,506 filed on Sep. 2, 2014.

FIELD OF THE INVENTION

The invention relates generally to speech recognition software and techniques and more specifically to a system and method for providing a dynamic teleprompter application for automatically scrolling the text of a speech given by a user based on speech recognition.

BACKGROUND OF INVENTION

Teleprompters are known in the art. Those speaking publicly may utilize a teleprompter to read from when giving a speech. The teleprompter displays the words of the script from which the reader is to read aloud. Teleprompters normally scroll through the script manually as chosen by a speaker. When a teleprompter is set at a constant rate the reader may fall behind the script and get lost or may read faster than the script and have to wait for the script to catch up. When a speaker moves the script manually and the speaker goes off script for a period of time, the speaker may forget to progress the script when the speaker goes back on script. Additionally, if a speaker wishes to jump ahead and skip a certain section then it would be difficult to quickly jump ahead to the specific section manually. What is needed is a system and method by which a written script is tracked and presented to a reader by recognizing the words that are being spoken orally and presenting the section of the script being read or heard at that time.

SUMMARY OF THE INVENTION

The following presents a simplified summary in order to provide a basic understanding of some aspects of the disclosed innovation. This summary is not an extensive overview, and it is not intended to identify key/critical elements or to delineate the scope thereof. Its sole purpose is to present some concepts in a simplified form as a prelude to the more detailed description that is presented later.

The invention is directed toward a computer-implemented method for dynamically presenting a prewritten text in a graphical user interface. The method comprises receiving a text artifact, the text artifact containing a plurality of artifact words, storing, via a processor, the text artifact in a memory device of a computer, retrieving, via the processor, the text artifact, displaying the text artifact on the display screen of the computer, receiving a vocal input, generating, via the processor, a text file representing the words spoken in the vocal input, the text file containing a plurality of hypothesis words, comparing, via the processor, a predetermined number of the hypothesis words to a predetermined number of the artifact words, determining a match location in the text artifact where a specific number of the predetermined number of hypothesis words match a specific number of the predetermined number of artifact words, and altering, via the processor, the display on the display screen to display the match location on the display screen of the computer. The method may further comprise highlighting on the display of

2

the computer screen one or more artifact words within the match location of the text artifact.

The method of highlighting may comprise altering the font of one or more artifact words on the display screen, altering the color of the font of one or more artifact words on the display screen, or creating a rectangular box surrounding one or more artifact words on the display screen of the computer.

The method may further comprise determining whether one or more words of the plurality of hypothesis words have been matched to a match location of the text artifact and removing one or more words from the plurality of hypothesis words, wherein the removed words have been previously matched to a match location of the text artifact. The method may further comprise determining whether the plurality of hypothesis words number four or more.

The method may further comprise retrieving twenty words of the text artifact following the match location and comparing, via the processor, a predetermined number of the hypothesis words to the twenty words of the text artifact following the match location.

The method may further comprise determining, via the processor, the font size of the text of the text artifact as displayed on the display screen, determining, via the processor, the orientation of the electronic screen displaying the text of the text artifact, and altering, via the processor, the predetermined number of artifact words utilized for comparing to the predetermined number of hypothesis words.

In one embodiment of the invention the step of comparing the predetermined number of the hypothesis words to the predetermined number of the artifact words comprises creating a first group containing the predetermined number of hypothesis words, creating a second group containing the predetermined number of artifact words, the second group being displayed on the display screen of the computer, respectively determining whether each of the predetermined number of hypothesis words is present in the first group, respectively determining whether each of the predetermined number of artifact words is present in the first group, and generating a single number, wherein the single number is representative of the degree of similarity between the first group and the second group.

In another embodiment of the invention the method may further comprise determining two or more second groups of the predetermined number of artifact words having a generated single number greater than a predetermined number, creating a list of all bigrams contained in the predetermined number of hypothesis words, creating a list of all trigrams contained in the predetermined number of hypothesis words, respectively creating a list of all bigrams contained in each of the two or more second groups, respectively creating a list of all trigrams contained in each of the two or more second groups, respectively comparing each list of bigrams of the two or more second groups to the list of all bigrams contained in the predetermined number of hypothesis words, respectively comparing each list of trigrams of the two or more second groups to the list of all trigrams contained in the predetermined number of hypothesis words, determining one of the two or more second groups of the predetermined number of artifact words having the greatest total number of bigrams and trigrams present in the list of all bigrams and the list of all trigrams contained in the predetermined number of hypothesis words, selecting the one of the two or more second groups of the predetermined number of artifact words having the greatest total number of bigrams and trigrams present in the list of all bigrams and the list of all trigrams contained in the predetermined number of hypothesis words.

US 9,953,646 B2

3

esis words, and selecting a portion of the text artifact, wherein the selected portion of text artifact contains the selected one of the two or more second groups of the predetermined number of artifact words having the greatest total number of bigrams and trigrams present in the list of all bigrams and the list of all trigrams contained in the predetermined number of hypothesis words.

In another embodiment of the invention the method may further comprise establishing a scroll rate for the text artifact on the display screen of the computer. The method may further comprise increasing the scroll rate when a speaker's location in the text artifact is ahead of the highlighting. The method may further comprise decreasing the scroll rate when a speaker's location in the text artifact is behind the highlighting.

Still other embodiments of the present invention will become readily apparent to those skilled in this art from the following description wherein there is shown and described the embodiments of this invention, simply by way of illustration of the best modes suited to carry out the invention. As it will be realized, the invention is capable of other different embodiments and its several details are capable of modifications in various obvious aspects all without departing from the scope of the invention. Accordingly, the drawing and descriptions will be regarded as illustrative in nature and not as restrictive.

BRIEF DESCRIPTION OF THE DRAWINGS

Various exemplary embodiments of this invention will be described in detail, wherein like reference numerals refer to identical or similar components, with reference to the following figures, wherein:

- FIG. 1 is a view of the system of the invention;
- FIG. 2 is a view of the system of the invention;
- FIG. 3 is a view of a text artifact;
- FIG. 4A is a view of a device utilizing the invention;
- FIG. 4B is a view of a device utilizing the invention;
- FIG. 5 is a schematic displaying the method of the invention;
- FIG. 6 is a schematic displaying the method of the invention;
- FIG. 7 is a schematic displaying the method of the invention;
- FIG. 8 is a schematic displaying the method of the invention;
- FIG. 9 is a schematic displaying the method of the invention; and
- FIG. 10 is a view of a device utilizing the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The claimed subject matter is now described with reference to the drawings. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the claimed subject matter. It may be evident, however, that the claimed subject matter may be practiced with or without any combination of these specific details, without departing from the spirit and scope of this invention and the claims.

As used in this application, the terms "component", "module", "system", "interface", or the like are generally intended to refer to a computer-related entity, either hardware, a combination of hardware and software, software, or software in execution. For example, a component may be, but is not limited to being, a process running on a processor,

4

a processor, an object, an executable, a thread of execution, a program, and/or a computer. By way of illustration, both an application running on a controller and the controller can be a component.

The invention pertains to a method and system utilizing speech recognition to locate a specific location in a prewritten script (also known as a text artifact). The method may further provide for graphically presenting a section of the prewritten script to a user. The graphical representation of the prewritten script may display any amount of the prewritten script. In the preferred embodiment, the graphical presentation of the prewritten script displays the section where the speech recognition locates the speaker as reading from. The speaker's place may be highlighted or otherwise shown in a distinctive manner. In the preferred embodiment a small section of the prewritten script before this location is displayed and a small portion of the prewritten script after this section is displayed. These three portions may be of any size and display any number of words. In this method a computer system and program is utilized to receive an auditory input of spoken words. The computer system then creates a number of hypotheses about the words being spoken. The computer system cross references the hypotheses of the spoken words with the prewritten script. The computer system then locates the specific section of the prewritten script from where the words are being spoken. The system and method may be used for any purpose, on any computerized device, including but not limited to a desktop computer, a laptop computer, a tablet computer, a wireless cellular phone, or any other computerized device. The specific manner utilized to perform the method of the invention may be any number of ways. There may be variations in the specific mechanisms utilized without varying from the scope of the invention.

The software utilized for performing the invention may have a multitude of additional features. The system and method of the invention may be practiced with or without the additional features. The software may allow for a user to create an audio recording of any speech as it is given. The system stores the audio file of the recording in a file which may be associated with the prewritten script. The software may allow for a user to turn off the automatic scrolling function so that the user can scroll manually through the prewritten script. Alternatively, the user may set the prewritten script to advance at a set rate. The set rate may be any number of words per minute as desired by the user. The software may utilize a clock or timer. The timer can display the total time that the speaker has been speaking for. Alternatively, the user can input a set time as a time limit for the speech. The timer will then count down, displaying the time left, and will alert the user when the remaining time has run out and the user is out of speaking time. The system may allow a user to type a prewritten script directly into the software application and store for later utilization. Alternatively, the user may type a prewritten script in a separate software application and then utilize the file created in the software. The user may customize the settings of the software, such as standard font size and microphone sensitivity levels. The system may permit the user to create a password protected user ID to utilize the software. The system may permit the user to only view the prewritten scripts associated with that user's user ID. Multiple users may utilize the software system on a single device by each having a unique user ID. The system may permit users to share prewritten scripts with other users. The system may permit a user to friend other users of the system. The system may store prewritten scripts on a third party server and permit a user

US 9,953,646 B2

5

to store and retrieve prewritten scripts remotely through an internet connection. The software may contain a search function. The search function may permit a user to search through titles of prewritten scripts. The search function may permit a user to search through the content of multiple prewritten scripts to find prewritten scripts containing specific keywords and choose one for presentation. The search function may permit a user to search for a keyword or phrase within a prewritten script during the reading of the prewritten script. This function would permit the user to search and find a specific section of the prewritten script so the user may start reading from that section.

Although the specific manner of performing the method may be performed through a number of separate embodiments, only the preferred embodiment will be described in detail. In the preferred embodiment, a speech recognition algorithm recognizes the words being spoken by a user and creates a series of hypotheses of the words being spoken. A matching algorithm matches the hypothesis generated to a prewritten script. The matching algorithm may make a match with any number of words or phonemes received. In the preferred embodiment, a minimum of three words is needed to match against the prewritten script. The matching algorithm may attempt to match the hypothesis received against any number of words or part of the prewritten script. In the preferred embodiment the algorithm attempts to match the hypothesis against the next twenty words in the prewritten script appearing after the last positive match. The match may be made with or without reference to the order of the words in the prewritten script. Thus if all words in a hypothesis are present in a portion of the prewritten script (even if not in the same order) then a positive match may be made. The matching algorithm may or may not authenticate the matched location. The algorithm may authenticate a positive match by verifying that the order of the words in the matched portion of the prewritten script is identical to the order of words in the hypothesis.

Referring to FIG. 1 and FIG. 2, the invention is performed on a computerized device 10 with a display screen 15. The display screen 15 displays the text artifact 100. In the preferred embodiment the display screen 15 is integral to the body of the computerized device 10. In other embodiments the display screen 15 is separate from the computerized device 10. The computerized device 10 receives the vocal input of the user through a microphone. The microphone may be integral to the body of the computerized device 10 or separate from the computerized device 10. The display screen 15 displays the text artifact 100 in accordance with the instructions from the computerized device 10. As shown in FIG. 1, the computerized device 10 may be a laptop style computer or, as shown in FIG. 2, the computerized device 10 may be a tablet style computer or smartphone.

At the heart of the matching algorithm is the ability for the app to take a hypothesis fed to it by the speech recognition algorithm and match it to the right piece of text within the script that corresponds to the user's current location in the script. As shown in FIG. 3, the text artifact 100 contains a plurality of lines of text 110. The matching algorithm determines the specific line of text 110 which the vocal input matches and adjusts the text artifact 100 on the display 15 of the computerized device 10. As shown in FIG. 4A and FIG. 4B, the computerized device 10 receives the vocal input of the speaker, matches the vocal input to a specific line of text 110, and highlights the location of the specific line of text 110 on the display screen 15. As shown in FIGS. 4A and 4B, the highlight 112 distinctly points out to the user the section from which the user is reading. As shown in FIG. 4A, the

6

highlight 112 is a colored box surrounding the specific line of text 110 of the text artifact 100 that the speaker is reading from. As the speaker progresses through the text artifact 100 the highlighting 112 progresses with the speaker. As shown in FIG. 4B, the highlighting 112 moves lower down the text artifact 100 on the display 15 of the computerized device 10.

The algorithm which is used to achieve this must also adhere to the following requirements:

Accurately match the last spoken hypothesis to the closest match to it in the text from the user's current location.

Discard any speech made by the user which does not correspond to any part of the text.

Avoid skipping forward in the document that might result of incorrectly matching the current hypothesis to the wrong text in the Script.

In the preferred embodiment, the matching algorithm relies on input generated by the speech recognition algorithm. As a user speaks, the speech recognition algorithm generates and passes hypotheses of the words it has detected to be spoken to the matching algorithm. As hypotheses are generated by the speech recognition algorithm, the matching algorithm attempts to match these to the words within the text being presented. The matching algorithm keeps track of the current line of text that the presenter is detected to be on and attempts to match the hypotheses generated by the speech recognition algorithm to the next 20 words of text from the line that the user is detected to be on.

For every hypothesis generated the matching algorithm performs the following processing steps:

Hypothesis Refinement

Cosine Distance Match

N-Gram Analysis Match

These processing steps may be performed independently from each other and not all steps must be performed. For instance, the algorithm may forego the hypothesis refinement or may forego the N-Gram analysis. The N-Gram analysis may only be performed if necessary.

Referring to FIG. 5, the broad method of the invention is displayed. First the computerized device receives and stores a text artifact of the speech to be read by the user 200. Then the computerized device receives the vocal input of the user 202. The computerized device then generates a hypothesis of the words spoken 204. The computerized device refines the hypothesis by removing words from the hypothesis which have been previously matched to the text artifact 206. The computerized device compares the hypothesis to the words in the text artifact 208. The computerized device then transitions the display of the text artifact to display the matched line of text and could highlight the matched line of text 210.

Referring to FIG. 6, the detailed embodiment of the method is displayed. First the computerized device derives a scoped hypothesis by subtracting the last matched hypothesis from the new hypothesis 300. The system then determines whether the scoped hypothesis contains at least four words 302. If the hypothesis does not contain at least four words then the system continues to receive vocal input until the scoped hypothesis contains at least four words. The system then extracts from the text artifact the next set of words which will be used to compare to the scoped hypothesis 304. The system performs a cosine distance matching function 306 and generates a number corresponding to the level of match between a specific section of the text artifact and the hypothesis. In the preferred embodiment, the system requires a minimum output number from the cosine distance matching function to determine a match from the hypothesis and a section of the text artifact. The system then determines

US 9,953,646 B2

7

whether there is a single possible match in the text artifact which has the minimum output number 308. If the system determines that there is a single section of text artifact with a match greater than the minimum required value then the system concludes that there is a match to that specific section of text in the text artifact 310. If there are multiple sections of text which have a score over the minimum level then the system performs an n-gram analysis on the highest three possible matches 312. The system then selects the section of the text artifact with the highest n-gram score and concludes that there is a match with the text artifact 314.

In the preferred embodiment of the hypothesis refinement, the following process is followed. A speech recognition algorithm generates hypotheses which are not mutually exclusive of each other. That is as a user speaks a sentence, the speech recognition algorithm may generate X hypotheses with each hypothesis being composed up of all words in the previous hypothesis appended with a single new word. The speech recognition algorithm may continue to generate hypotheses by appending newly detected words on an ongoing sentence or may reset and generate a hypothesis with just the last word it has detected.

The first step of the matching algorithm is to refine the hypothesis and pull out only those words which are new or which haven't been matched as part of the last hypothesis that was attempted to be matched by the matching algorithm. This scoped down hypothesis becomes the piece of text which is attempted to be matched against the next set of 20 words in the document. The algorithm will only attempt to match a scoped hypothesis which has at least 4 words, otherwise it skips processing of it and waits until a hypothesis can be created with at least 4 words.

For example, for the following text: "Turning once again, and this time more generally, to the question of invasion", the following hypotheses may be generated by a speech recognition algorithm as a user reads the text:

1. Turning
2. Turning once
3. Turning one
4. Turning once again
5. Turning once again an
6. Turning once again and this
7. Turning once again and this time
8. Turning once again and this time more generically
9. Turning once again and this time more generally to the
10. Turning once again and this time more generally to the question

In the preferred embodiment of the cosine distance matching, the following process is followed. Once a scoped down hypothesis has been generated by the matching algorithm the next step in the match algorithm is to look at the next X words of text in the document and attempt to determine a measurement of the similarity between the generated text and the text within the document. The value of X is variable and may be defined in any manner. In the preferred embodiment the value of X is defined based on the font size used and the device screen size.

The first part of the match algorithm uses a Cosine Distance Matching algorithm to break down the scoped hypothesis and the next 20 words of text in the document to measure the number of words between the two that match.

The pseudo code for the Cosine Distance algorithm resembles this:

Given an array H that contains the scoped hypothesis of length k words.

Given a vector V which contains each unique word in H and the number of times it appears in H.

8

Given an array T that contains the next X words of the text document.

- 1.) Retrieve the next k words of text from T, Tw.
- 2.) Create a vector Vw which is the same length as V.
- 3.) For every unique word in Tw which is also found in V, set the value in Vw at the same index to 1.
- 4.) Perform a dot-product calculation on Vw against V. If the dot product is greater than 0, then store the result for that window of text as Rw.
- 5.) Go to 1 and repeat until no more words in T to process.

At the end of this process, the algorithm has a list of all dot products (Rw) for each window of text from T that was analyzed. If the algorithm ends with more than 3 windows of text that have a non-zero dot product, the algorithm then uses N-Gram analysis to further analyze and identify the best match in the text.

If the algorithm ends with only 1 window of text that produces a non-zero dot product, then that window of text is determined to be the best match for the hypothesis H. If the algorithm outputs no windows of text with a non-zero dot product, then the hypothesis is not matched against any part of the text and processing stops until the next hypothesis is received.

This process is illustrated in FIG. 7. First the system retrieves the section of text artifact following the prior matched hypothesis 400. The system then creates a vector containing each unique word in the hypothesis and the number of times it appears in the hypothesis 402. The system then creates one or more vectors from the section of text artifact, with each vector having the same length as the hypothesis vector 404. The system then performs a dot-product calculation for each vector from the text artifact with the vector from the hypothesis 406. The system then selects the section of text from the text artifact having the highest dot-product calculation result 408. The system then scrolls the text artifact on the display screen of the device to prominently display the selected section of text from the text artifact 410. The system then may highlight the selected section of text from the artifact on the display screen of the device 412.

The following is an illustration of the cosine distance matching function performed by the system. The cosine distance matching function is represented by the following algorithm:

$$A \cdot B = \sum_{i=1}^n A_i B_i = A_1 B_1 + A_2 B_2 + \dots + A_n B_n$$

As represented in the function the hypothesis would be represented by A and the text artifact would be represented by B. The first word of the hypothesis would be represented by A₁, the second word of the hypothesis would be represented by A₂, and so on. The first word of the text artifact would be represented by B₁, the second word of the text artifact would be represented by B₂, and so on.

The number for each spot in the vector for the hypothesis is a 1 because the word is present in the text artifact. The words in the section of text artifact are then compared to the hypothesis. If the word in the text artifact is present in the hypothesis then the spot for that word is represented by a 1 in the vector. If the word is not present in the hypothesis then the spot for that word is represented by a zero. The dot product function then gives a number for that specific

US 9,953,646 B2

9

section of the text artifact. The higher the number as a result the more likely that specific section of text artifact is a match to the hypothesis.

As an illustration of the cosine distance matching function, and by no means limiting the scope of the invention, assume that the hypothesis of the vocal input is "The big dog bit the small dog." In this illustration the next section of text artifact to be matched is "The dog was bit on his leg." The system creates a vector of the hypothesis where $V = (\text{the, big, dog, bit, the, small, dog})$. Since each of these words are in the hypothesis then the numerical representation of the vector is $V = (1, 1, 1, 1, 1, 1, 1)$. The system creates a vector for the next section of text artifact where $Vw = (\text{the, dog, was, bit, on, his, leg})$. Represented numerically $Vw = (1, 1, 0, 1, 0, 0, 0)$. If a word in a specific spot is present in the hypothesis then it is represented by a 1. If it is not present then it is represented by a 0. The system performs a dot product of V and Vw . In this instance, $V \cdot Vw = (1 \times 1 + 1 \times 1 + 1 \times 0 + 1 \times 1 + 1 \times 0 + 1 \times 0 + 1 \times 0) = 1 + 1 + 0 + 1 + 0 + 0 + 0 = 3$. In this instance, the next section of text results in a dot product result of 3. If the next words in the text artifact are "The big dog bit the small dog" then the system performs a dot product in the same manner. The result of the dot product for this section of the text artifact is 7. Because 7 is greater than 3 the system determines a match at the section of text artifact reading "The big dog bit the small dog." The system then scrolls the display of the text artifact to display "The big dog bit the small dog" and further highlights the section of the text artifact containing the words "The big dog bit the small dog."

The Cosine Distance algorithm while giving a measure in the similarity of the two pieces of text contains no provision for the order of the words. Hence if there are 3 or more non-zero dot products, the algorithm performs N-Gram Analysis which does take into account the order of words to identify which window of text is the best match for the hypothesis.

In the preferred embodiment of the N-Gram analysis, the following process is followed. The N-Gram analysis takes as an input the top 3 candidate matches from the document outputted by the Cosine Distance formula and then analyzes them to identify which one of them best matches the scoped hypothesis taking into account the order of the words. The N-Gram analysis performs an analysis of the candidate matches and generates a score indicating the strength of the match that does take into account the order of the words. An example of how N-Gram analysis is performed is as follows:

Given a hypothesis H ,
A list of all bigrams in H : Bh
A list of all trigrams in H : Th
For each window of text Tw :
1.) Extract all the bigrams of Tw into Bw .
2.) Extract all the trigrams of Tw into $Triw$.
3.) Count the number of elements in Bw which match Bh .
4.) Count the number of elements in $Triw$ which match Th .
5.) Add the output of 3.) and 4.) and assign that as the N-gram score for Tw .

Once all the N-gram scores have been calculated, the algorithm chooses the window of text (Tw) which has the highest N-gram score to be the best match to the scoped hypothesis.

To improve the accuracy of the N-Gram score and to reduce the instances of false positives being matched (i.e. when the user goes off script, the algorithm needs to be smart enough to not generate any matches against the text), the N-Gram analysis filters and ignores any bigrams or trigrams that match any 1 of the 70 of the most common articles

10

found in the English language. Any N-gram which is generated that matches one of the articles in this list of 70 is ignored by the analysis and does not contribute to the final scoring.

The N-gram analysis process is illustrated in FIG. 8. The system first determines that there are multiple sections of the text artifact as possible matches to the hypothesis 500. The system then generates a list of all bigrams in the hypothesis 502. The system then generates a list of all trigrams in the hypothesis 504. The system generates a list of all bigrams in each respective section of text artifact 506. The system then generates a list of all trigrams in each respective section of text artifact 508. The system then compares the bigrams and trigrams of the hypothesis to the bigrams and trigrams of each respective section of the text artifact 510. The system then determines the section of text artifact with the highest number of bigram and trigram matches to the hypothesis 512. In this process the order of the words are taken into account. The bigrams are composed of two phonemes, two syllables, or two words which are presented in side by side in direct progression. The trigrams are composed of three phonemes, three syllables, or three words which are presented in direct order.

In the preferred embodiment at the end of the Cosine Distance and N-Gram analysis, the matching algorithm takes the window of text Tw that is determined to be the best match against the hypothesis and identifies the line number in the document that that window corresponds to. Once the algorithm has detected that it is on a particular line of text in the document then the next time a hypothesis is analyzed it will only attempt to match against words of text taken from the next line.

In one embodiment of the invention, the process is performed by a computer matching algorithm. A separate algorithm receives an auditory input of a speaker's voice and creates a series of hypotheses of the words being spoken. The matching algorithm receives an input of these series of hypotheses of the spoken words. The matching algorithm then performs the following steps—

- 1.) Derive a scoped hypothesis which is the subtraction of the last matched hypothesis from the new hypothesis.
- 2.) Does the scoped hypothesis have at least 4 words in it? If yes, continue to 3. If no, then stop processing and wait for the next hypothesis.
- 3.) Extract from the artifact the next set of words which will be used to compare the scoped hypothesis against.
- 4.) Perform Cosine Distance matching step
- 5.) Did the Cosine Distance step produce a single possible match with a distance score of at least 3.0? If yes, then we conclude that the scoped hypothesis to be matched on the line of text that begins the possible match, we increment the current line marker and wait for the next hypothesis. If no and there are more than 1 possible matches, continue to 6.). If no and there are no possible matches with a score of at least 3.0, then stop processing and wait for the next hypothesis.
- 6.) Take the top 3 possible matches from the Cosine Distance step and perform an N-Gram analysis.
- 7.) Select the possible match which has the highest score in the N-Gram analysis and conclude that the scoped hypothesis to be matched on the line of text that the possible match begins on. Increment the current line marker and wait for the next hypothesis to process.

In a separate component of the method and system, the invention provides for the ability to dynamically change the start location of the prewritten script. This component permits the user to pause and restart of the tracking of the

US 9,953,646 B2

11

reading of the prewritten script. The software tracks the location of the prewritten script from where the user is reading. The user may view the prewritten script on a computerized presentation device with a touch screen user interface. The user may move the location of the prewritten script by touching the touch screen user interface and dragging through the prewritten script to a different location. The user may scroll through the prewritten script manually in this manner. The user may scroll forward in the prewritten script to skip a certain section or may scroll backward in the prewritten script to review or repeat a prior section. In this component the speech recognition software automatically tracks the movement made by the user and resets to track the speech of the user from the location that the user moved to. The software tracks this move by the user automatically without the user needing to reset the starting or tracking point.

In a specific example of the utilization of this component, and by no means limiting the scope of this component, a user may start at the first paragraph of a prewritten script. The system tracks the location of the speaker as the speaker reads from the first paragraph. If, when the speaker reaches the second paragraph, the speaker decides to skip the second paragraph and read from the third paragraph, the user can touch the screen and swipe the prewritten script forward to the third paragraph. The speaker then starts reading from the prewritten script at the third paragraph. The system starts tracking the location that the speaker is reading from and presenting the third paragraph of the prewritten script to the user. The software automatically starts tracking from this new location.

In a separate component of the invention, the method and system provide for highlighting a specific word, region, or portion of the prewritten script that is matched by the speech recognition software. The highlighting method is performed in real time as the speaker reads from the prewritten script. The highlighting is performed by the software as a means of presenting to the speaker the portion of the prewritten script that the speaker is reading from so that the speaker may keep track of the speaker's location during reading from the prewritten script. In one specific example of one embodiment of this component, and in no way limiting the scope of this component, the method performed by this component matches the location of the prewritten script from which the speaker is reading. The software then presents the location of the prewritten script that the speaker is reading from in highlighted format. For instance, the highlighted section may be presented on a line by line basis. The line before the line from which the speaker is reading is presented in normal format. The line after the line from which the speaker is reading is presented in normal format. The line between the two, the line from which the speaker is reading, is presented in a highlighted format. As the reader progresses reading through the prewritten script the highlighted format progresses through the prewritten script along with the speaker. As the speaker reaches the next line the highlighted formatting moves to the next line as well. The prior line which was highlighted as the speaker read from it is no longer presented in a highlighted format once the speaker is no longer reading from that line of the prewritten script. In other embodiments of this component, the highlighted formatting may be presented on a word by word basis rather than line by line. In another embodiment, the highlighting formatting is set to present the words which the speaker has already read in a highlighted formatting so the speaker may know what words have already been read. In another embodiment, the highlighted formatting may be presented on a section by section

12

basis. The section highlighted may be any number of words or any number of lines of the prewritten script. The highlighted formatting may be completed in any type of format, such as changing the color of the text, changing the color of the background of the text, changing the font of the text, changing the size of the font of the text, presenting the text in bold, presenting the text in italics, or presenting the text in another format that is distinctive from the format of the rest of the text of the prewritten script.

In a separate component of the invention, the method and system provide for dynamically scrolling through the prewritten script of the speaker as the speaker is reading from the prewritten script. The scrolling method dynamically adjusts based on the speaker's actual position in the text. The method provides that the text scrolls smoothly from line to line as the speaker reads from the prewritten script. The pace of the scrolling adjusts dynamically to the position of the speaker as the speaker reads from the prewritten script that is displayed on the graphical user interface. If the speaker is towards the bottom of the portion of the prewritten script displayed on the display then the system speeds up the pace of the scrolling quickens to catch up to the position of the speaker. If the speaker reads from the top of the portion of the prewritten script displayed on the display then the system slows down the pace of scrolling to allow the speaker to catch up to the prewritten script displayed in the middle portion of the display screen. This component permits the system to track and present the prewritten script in the proper manner to follow the pace of the speaker. Thus, the speaker can speak at the pace chosen by the speaker and the system will follow dynamically. Further, the speaker may change pace throughout the presentation of the speech and the system will follow the changes in pace made by the speaker.

The method of altering the scrolling of the text artifact is displayed in FIG. 9. First the system establishes a predetermined scroll rate for the text artifact to scroll on the device display screen 600. The system then determines the position of the speaker in the text artifact by determining the location of the text artifact where the hypothesis has been matched and its location on the screen of the computerized device. The system is configured to continuously present the location of the speaker in the text artifact within the middle section of the display screen of the computerized device. The system then determines whether the central portion of the text artifact displayed on the screen of the computerized device is behind the position of the speaker (or the location of the hypothesis match in the text artifact) 602. If the central displayed section is behind the position of the speaker then the system accelerates the scrolling 604. The system then determines whether the central displayed section is far behind the speaker's position 606. If the central displayed section is far behind the position of the speaker then the system accelerates the rate progressively and advances the text artifact 608. If the central displayed section is not far behind the position of the speaker then the system accelerates the scrolling incrementally and advances the text artifact 610. If the central displayed section is not behind the position of the speaker, but is instead ahead of the speaker's position then the system decelerates the scrolling 612. The system then determines whether the central displayed section is far ahead of the speaker's position 614. If the system determines that the central displayed section is not far ahead of the speaker's position then the system decelerates the scrolling incrementally and advances the text artifact 616. If the system determines that the central displayed section is

US 9,953,646 B2

13

far ahead of the speaker's position then the system decelerates progressively and stops the scrolling of the text artifact 618.

Referring to FIG. 10, the scrolling method of the invention is further illustrated. The display screen 15 prominently displays the central displayed section 700 in the center of the display screen 15. In the preferred embodiment the matched hypothesis is continuously located within the central display section 700. If the system determines that the matched hypothesis is located in the top display section 710 then the system automatically increases the scrolling rate of the text artifact 100 on the display screen 15. If the system determines that the matched hypothesis is located in the bottom display section 720 then the system automatically decreases or stops the scrolling rate of the text artifact 100 on the display screen 15.

In a separate component of the invention, the method and system automatically adjust the presentation of the prewritten script based on manual adjustments made by the user on the graphical display of the device. In this component, the user may touch and the graphical display of the device displaying the prewritten script. In one embodiment of this component, the user utilizes a computerized device with a touch screen display. The user can use two fingers to touch the touch screen display and pinch the screen to zoom out. The user can zoom in on the prewritten script by moving both fingers in opposite directions. When a user utilizes the zoom in and out feature the software automatically adjusts the text size of the prewritten script. In one example of an embodiment of this component, and by no means limiting the scope of this component, a user touches the touch screen display with two fingers and moves both fingers apart. This move enacts the zoom in feature. The font of the prewritten script would thus change and get larger. Alternatively, the user may touch the touch screen display with two fingers and pinch the two fingers together. This move enacts the zoom out feature. The font of the prewritten script would thus change and get smaller. The zoom feature may occur in a multitude of embodiments. For instance, when zooming out the display may show additional lines of the prewritten script that were not viewable on the display screen before zooming out. Alternatively, the display may still only show the original lines of the prewritten script without adding lines which were not viewable before zooming out. In another embodiment, the zoom feature may rearrange the number of words present on each line of the prewritten script as displayed on the display screen. In this embodiment, when a user zooms in the words which were all on one line may rearrange so that the words at the end of the line move below to the next line and start the next line of the prewritten script displayed. The words displayed on the remaining lines of the prewritten script are thus rearranged so that the total number of words displayed on each line decrease. Alternatively, in this embodiment, when a user zooms out the words which were on multiple lines rearrange so that the words on the multiple lines combine onto one line. In this manner, words which had started a second line move after the words at the end of the prior line.

Another component of the invention is a modification of the matching algorithm based on the manual zoom performed by the user. The matching algorithm starts with the creation of a scoped down hypothesis. When a user zooms in or zooms out, the first word of a line changes. The matching algorithm then automatically resets the start position from where it creates hypotheses to the new first word of the line. The matching algorithm may begin to create a new hypothesis which overlaps, fully or partially, with any

14

old hypothesis created prior to the user zooming in or zooming out. The matching algorithm can thus reset and start tracking from the new word position automatically without requiring the user to reset the tracking position. The matching algorithm correctly calibrates based on the size of the font and specific graphical view of the script utilized by a user.

Each of these components may exist independently of the other components. Each component may be utilized separate from method utilized to track the prewritten script with speech recognition.

The methods, systems, and components above may be utilized in any fashion and for any purpose. In the preferred embodiment the methods are utilized as methods for a teleprompter. However, other natural uses for the methods may be self-evident as other embodiments without departing from the invention. For instance, and without limiting the scope of the invention, the methods, systems, and components may be utilized for a closed captioning system, a teletype device, TTY or TDD, game, or any other type of auditory device or system or software program utilizing audio.

What has been described above includes examples of the claimed subject matter. It is, of course, not possible to describe every conceivable combination of components or methodologies for purposes of describing the claimed subject matter, but one of ordinary skill in the art can recognize that many further combinations and permutations of such matter are possible. Accordingly, the claimed subject matter is intended to embrace all such alterations, modifications and variations that fall within the spirit and scope of the appended claims. Furthermore, to the extent that the term "includes" is used in either the detailed description or the claims, such term is intended to be inclusive in a manner similar to the term "comprising" as "comprising" is interpreted when employed as a transitional word in a claim.

The foregoing method descriptions and the process flow diagrams are provided merely as illustrative examples and are not intended to require or imply that the steps of the various embodiments must be performed in the order presented. As will be appreciated by one of skill in the art the order of steps in the foregoing embodiments may be performed in any order. Words such as "thereafter," "then," "next," etc. are not intended to limit the order of the steps; these words are simply used to guide the reader through the description of the methods. Further, any reference to claim elements in the singular, for example, using the articles "a," "an" or "the" is not to be construed as limiting the element to the singular.

The various illustrative logical blocks, modules, circuits, and algorithm steps described in connection with the embodiments disclosed herein may be implemented as electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. Skilled artisans may implement the described functionality in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the present invention.

The hardware used to implement the various illustrative logics, logical blocks, modules, and circuits described in connection with the aspects disclosed herein may be imple-

US 9,953,646 B2

15

mented or performed with a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but, in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices, e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. Alternatively, some steps or methods may be performed by circuitry that is specific to a given function.

In one or more exemplary aspects, the functions described may be implemented in hardware, software, firmware, or any combination thereof. If implemented in software, the functions may be stored on or transmitted over as one or more instructions or code on a computer-readable medium. The steps of a method or algorithm disclosed herein may be embodied in a processor-executable software module, which may reside on a tangible, non-transitory computer-readable storage medium. Tangible, non-transitory computer-readable storage media may be any available media that may be accessed by a computer. By way of example, and not limitation, such non-transitory computer-readable media may comprise RAM, ROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium that may be used to store desired program code in the form of instructions or data structures and that may be accessed by a computer. Disk and disc, as used herein, includes compact disc (CD), laser disc, optical disc, digital versatile disc (DVD), floppy disc, and blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers. Combinations of the above should also be included within the scope of non-transitory computer-readable media. Additionally, the operations of a method or algorithm may reside as one or any combination or set of codes and/or instructions on a tangible, non-transitory machine readable medium and/or computer-readable medium, which may be incorporated into a computer program product.

The preceding description of the disclosed embodiments is provided to enable any person skilled in the art to make or use the present invention. Various modifications to these embodiments will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other embodiments without departing from the spirit or scope of the invention. Thus, the present invention is not intended to be limited to the embodiments shown herein but is to be accorded the widest scope consistent with the following claims and the principles and novel features disclosed herein.

The invention claimed is:

1. A computer-implemented method for dynamically presenting a prewritten text in a graphical user interface comprising

- a) receiving a text artifact, said text artifact containing a plurality of artifact words;
- b) storing, via a processor, said text artifact in a memory device of a computer;
- c) retrieving, via said processor, said text artifact;
- d) displaying said text artifact on the display screen of said computer;
- e) receiving a vocal input;

16

- f) generating, via said processor, a text file representing the words spoken in said vocal input, said text file containing a plurality of hypothesis words;
 - g) comparing, via said processor, a predetermined number of said hypothesis words to a predetermined number of said artifact words;
 - h) determining a match location in said text artifact where a specific number of said predetermined number of hypothesis words match a specific number of said predetermined number of artifact words;
 - i) altering, via said processor, the display on said display screen to display said match location on said display screen of said computer;
 - j) determining, via said processor, the font size of the text of said text artifact as displayed on said display screen;
 - k) determining, via said processor, the orientation of the electronic screen displaying the text of the text artifact;
 - l) altering, via said processor, said predetermined number of artifact words utilized for comparing to said predetermined number of hypothesis words.
2. The method as in claim 1 further comprising highlighting on said display of said computer screen one or more artifact words within said match location of said text artifact.
3. The method as in claim 2 wherein said method of highlighting comprises altering the font of one or more artifact words on said display screen.
4. The method as in claim 2 wherein the method of highlighting comprises altering the color of the font of one or more artifact words on said display screen.
5. The method as in claim 2 wherein the method of highlighting comprises creating a rectangular box surrounding one or more artifact words on said display screen of said computer.
6. The method as in claim 1 further comprising
- a) determining whether one or more words of said plurality of hypothesis words have been matched to a match location of said text artifact;
 - b) removing one or more words from said plurality of hypothesis words, wherein said removed words have been previously matched to a match location of said text artifact.
7. The method as in claim 6 further comprising determining whether said plurality of hypothesis words number four or more.
8. The method as in claim 1 further comprising
- a) retrieving twenty words of said text artifact following said match location;
 - b) comparing, via said processor, a predetermined number of said hypothesis words to said twenty words of said text artifact following said match location.
9. The method as in claim 1 further comprising establishing a scroll rate for said text artifact on said display screen of said computer.
10. The method as in claim 9 further comprising increasing said scroll rate when a speaker's location in said text artifact is positioned at a bottom portion of the display screen.
11. The method as in claim 9 further comprising decreasing said scroll rate when a speaker's location in said text artifact is positioned at a top portion of the display screen.
12. A computer-implemented method for dynamically presenting a prewritten text in a graphical user interface comprising
- a) receiving a text artifact, said text artifact containing a plurality of artifact words;
 - b) storing, via a processor, said text artifact in a memory device of a computer;

US 9,953,646 B2

17

- c) retrieving, via said processor, said text artifact;
 - d) displaying said text artifact on the display screen of said computer;
 - e) receiving a vocal input;
 - f) generating, via said processor, a text file representing the words spoken in said vocal input, said text file containing a plurality of hypothesis words;
 - g) comparing, via said processor, a predetermined number of said hypothesis words to a predetermined number of said artifact words, wherein comparing said predetermined number of said hypothesis words to said predetermined number of said artifact words comprises
 - i) creating a first group containing said predetermined number of hypothesis words;
 - ii) creating a second group containing said predetermined number of artifact words, said second group being displayed on said display screen of said computer;
 - iii) respectively determining whether each of said predetermined number of hypothesis words is present in said first group;
 - iv) respectively determining whether each of said predetermined number of artifact words is present in said first group;
 - v) generating a single number, wherein said single number is representative of the degree of similarity between said first group and said second group;
 - h) determining a match location in said text artifact where a specific number of said predetermined number of hypothesis words match a specific number of said predetermined number of artifact words;
 - i) altering, via said processor, the display on said display screen to display said match location on said display screen of said computer.
13. The method as in claim 12 further comprising highlighting on said display of said computer screen one or more artifact words within said match location of said text artifact.
14. The method as in claim 12 further comprising establishing a scroll rate for said text artifact on said display screen of said computer.
15. A computer-implemented method for dynamically presenting a prewritten text in a graphical user interface comprising
- a) receiving a text artifact, said text artifact containing a plurality of artifact words;
 - b) storing, via a processor, said text artifact in a memory device of a computer;
 - c) retrieving, via said processor, said text artifact;
 - d) displaying said text artifact on the display screen of said computer;
 - e) receiving a vocal input;
 - f) generating, via said processor, a text file representing the words spoken in said vocal input, said text file containing a plurality of hypothesis words;
 - g) comparing, via said processor, a predetermined number of said hypothesis words to a predetermined number of said artifact words;
 - h) determining a match location in said text artifact where a specific number of said predetermined number of hypothesis words match a specific number of said predetermined number of artifact words;
 - i) altering, via said processor, the display on said display screen to display said match location on said display screen of said computer;
 - j) determining two or more second groups of said predetermined number of artifact words having a generated single number greater than a predetermined number;

18

- k) creating a list of all bigrams contained in said predetermined number of hypothesis words;
 - l) creating a list of all trigrams contained in said predetermined number of hypothesis words;
 - m) respectively creating a list of all bigrams contained in each of said two or more second groups;
 - n) respectively creating a list of all trigrams contained in each of said two or more second groups;
 - o) respectively comparing each list of bigrams of said two or more second groups to said list of all bigrams contained in said predetermined number of hypothesis words;
 - p) respectively comparing each list of trigrams of said two or more second groups to said list of all trigrams contained in said predetermined number of hypothesis words;
 - q) determining one of said two or more second groups of said predetermined number of artifact words having the greatest total number of bigrams and trigrams present in said list of all bigrams and said list of all trigrams contained in said predetermined number of hypothesis words;
 - r) selecting said one of said two or more second groups of said predetermined number of artifact words having the greatest total number of bigrams and trigrams present in said list of all bigrams and said list of all trigrams contained in said predetermined number of hypothesis words;
 - s) selecting a portion of said text artifact, wherein said selected portion of text artifact contains said selected one of said two or more second groups of said predetermined number of artifact words having the greatest total number of bigrams and trigrams present in said list of all bigrams and said list of all trigrams contained in said predetermined number of hypothesis words.
16. The method as in claim 15 further comprising highlighting on said display of said computer screen one or more artifact words within said match location of said text artifact.
17. The method as in claim 15 further comprising establishing a scroll rate for said text artifact on said display screen of said computer.
18. A computer-implemented method for dynamically presenting a prewritten text in a graphical user interface comprising, on a computer comprising a microprocessor, a visual display, and a nonvolatile memory unit, said nonvolatile memory unit storing instructions which when executed by said microprocessor cause the computer to perform operations comprising
- a) receiving a text artifact, said text artifact containing a plurality of artifact words;
 - b) storing, via a processor, said text artifact in a memory device of a computer;
 - c) retrieving, via said processor, said text artifact;
 - d) displaying said text artifact on the display screen of said computer;
 - e) receiving a vocal input;
 - f) generating, via said processor, a text file representing the words spoken in said vocal input, said text file containing a plurality of hypothesis words;
 - g) comparing, via said processor, a predetermined number of said hypothesis words to a predetermined number of said artifact words;
 - h) determining a match location in said text artifact where a specific number of said predetermined number of hypothesis words match a specific number of said predetermined number of artifact words;

US 9,953,646 B2

19

- i) altering, via said processor, the display on said display screen to display said match location on said display screen of said computer;
 - j) determining whether one or more words of said plurality of hypothesis words have been matched to a match location of said text artifact;
 - k) removing one or more words from said plurality of hypothesis words, wherein said removed words have been previously matched to a match location of said text artifact;
 - l) determining, via said processor, the font size of the text of said text artifact as displayed on said display screen;
 - m) determining, via said processor, the orientation of the electronic screen displaying the text of the text artifact;
 - n) altering, via said processor, said predetermined number of artifact words utilized for comparing to said predetermined number of hypothesis words.
19. The method as in claim 18
- a) wherein comparing said predetermined number of said hypothesis words to said predetermined number of said artifact words comprises
 - i) creating a first group containing said predetermined number of hypothesis words;
 - ii) creating a second group containing said predetermined number of artifact words, said second group being displayed on said display screen of said computer;
 - iii) respectively determining whether each of said predetermined number of hypothesis words is present in said first group;
 - iv) respectively determining whether each of said predetermined number of artifact words is present in said first group;
 - v) generating a single number, wherein said single number is representative of the degree of similarity between said first group and said second group;
 - b) said method further comprising
 - i) determining two or more second groups of said predetermined number of artifact words having a generated single number greater than a predetermined number;

20

- ii) creating a list of all bigrams contained in said predetermined number of hypothesis words;
 - iii) creating a list of all trigrams contained in said predetermined number of hypothesis words;
 - iv) respectively creating a list of all bigrams contained in each of said two or more second groups;
 - v) respectively creating a list of all trigrams contained in each of said two or more second groups;
 - vi) respectively comparing each list of bigrams of said two or more second groups to said list of all bigrams contained in said predetermined number of hypothesis words;
 - vii) respectively comparing each list of trigrams of said two or more second groups to said list of all trigrams contained in said predetermined number of hypothesis words;
 - viii) determining one of said two or more second groups of said predetermined number of artifact words having the greatest total number of bigrams and trigrams present in said list of all bigrams and said list of all trigrams contained in said predetermined number of hypothesis words;
 - ix) selecting said one of said two or more second groups of said predetermined number of artifact words having the greatest total number of bigrams and trigrams present in said list of all bigrams and said list of all trigrams contained in said predetermined number of hypothesis words;
 - x) selecting a portion of said text artifact, wherein said selected portion of text artifact contains said selected one of said two or more second groups of said predetermined number of artifact words having the greatest total number of bigrams and trigrams present in said list of all bigrams and said list of all trigrams contained in said predetermined number of hypothesis words.
20. The method as in claim 19 further comprising establishing a scroll rate for said text artifact on said display screen of said computer.

* * * * *